



# ECOS



## ECOS 302 / ECOS 302 YF

### CHARACTERISTICS

	ECOS 302	ECOS 302 YF
	SCE302R	SCE302H
TYPE OF REFRIGERANT		
AUTOMATIC WORKING CYCLE No manual taps	•	•
HIGH PRECISION RECOVERY FUNCTION	•	•
AUTOMATIC OIL INJECTION refillable/hermetic bottles <b>(OIL LOCK)</b>	•	•
AUTOMATIC DYE INJECTION refillable/hermetic bottles <b>(OIL LOCK)</b>	✓	✓
HEATER BELT INCLUDED	•	•
USB PORT	•	•
INTERNAL DATA BASE including commercial and agricultural vehicles	•	•
INTEGRATED AUTOMATIC NITROGEN AND FORMING GAS LEAK CHECK <b>(CFU-NITRO / CFU-NITRO.HD.XX)</b>	✓	✓
INTERNAL FLUSHING	•	•
READY TO USE ON HYBRID OR ELECTRIC CARS with rapid oil decontamination system	•	•
CONFIGURABLE GAS TYPE from HFO1234YF to --> R134a	•	•
BLUETOOTH CONNECTION APP OKSY <sup>®</sup> GEN+	•	•



• STANDARD SUPPLY ✓ OPTION

### ACCESSORIES

	CODE	DESCRIPTION	ECOS 302	ECOS 302 YF
	ACC-88.072	Gas bottle adapter 1/4	✓	
	ACC-88.011	Straight adapter HP 1/4	✓	
	ACC-88-289H	Universal bottle adapter HFO1234YF		✓
	O-PK00051 O-PK00051 OPZ	Printer kit	✓	✓
	ACC-BLK-ECOS300	Antidust Blanket	✓	✓



1/2021

## NITROGEN LEAK CHECK OR HYDRO-NITROGEN

**CODE**

CFU-NITRO




Kit for the connection of 1 or 2.2 liter cylinders to the A/C station - Including:

- Carrying case
- Pressure reducer for 1 and 2.2 liter bottles
- Manifold for the A/C service station connection

**CODE**

CFU-NITRO.HD.XX



Kit for connection of 200 bar bottle to A/C Station - Inclusive of:

- Carrying case
- Pressure reducer 200 Bar
- Adapter for the connection to 1 and 2,2 L bottles
- Manifold for the A/C service station connection

# RANGE

R134a



R1234yf

**MODEL****ECOS 302****ECOS 302 YF**

### TECHNICAL FEATURES

<b>Display</b>	Graphic LCD 128x64 Pixel	Graphic LCD 128x64 Pixel
<b>Full Recovery Function</b>	YES	YES
<b>Tank Capacity</b>	9 Kg	9 Kg
<b>Heater Belt</b>	YES	YES
<b>Scale Accuracy</b>	+/- 5 g	+/- 5 g
<b>Compressor</b>	10 cc	10 cc
<b>Vacuum Pump</b>	50 l/min	50 L/min
<b>Air Purge</b>	Automatic	Automatic
<b>Power Supply</b>	220V 50 Hz	220V 50 Hz
<b>Dimensions</b>	51x48x94 cm	52x56x99 cm
<b>Weight</b>	55/64 Kg	57/66 Kg
<b>Packaging dimensions</b>	54x58x116 cm	54x58x116 cm

### SCOPE OF DELIVERY

<b>Hp LP Quick Couplers</b>	Included	Included
<b>Hoses</b>	3m	3m
<b>Blanket</b>	Option	Option
<b>Power Cord</b>	YES	YES
<b>Calibration Handle</b>	YES	YES
<b>Extra oil bottle</b>	YES	YES
<b>2 x temperature probes</b>	NO	NO

**Oksys****TOTAL DESIGN FOR BEST PERFORMANCE**